

# ANPR Mobile

Automatic Number Plate Reader



## APPLICATIONS

- ▼ Police enforcement
- ▼ Crime prevention

## FEATURES

- ▼ Embedded license plate analysis (Ocr onboard)
- ▼ All in one: monochrome and color sensors, IR illuminator
- ▼ Real time processing: up to 60 fps
- ▼ Color video streaming: H.264 & MPEG4
- ▼ Wi-fi data transmission from the unit to the pc/tablet
- ▼ Gps onboard
- ▼ Waterproof housing
- ▼ Web server configuration and setup
- ▼ SD memory card up to 16 GByte





# ANPR Mobile

## SOFTWARE FEATURES

### LICENCE PLATE RECOGNITION

<b>OCR</b>	ANPR engine on board
<b>Grabbing</b>	Up to 60 fps

### CONFIGURATION

<b>Web Server</b>	Installation and configuration by Web Server on board
<b>TCP/IP Server</b>	Configuration and monitoring through TCP/IP protocol
<b>Date and Hour</b>	Synchronization via SNTP protocol or GPS
<b>Software Update</b>	Upgrading via Web Interface

### DATA TRANSMISSION

<b>FTP</b>	FTP Client to FTP Server mode for remote data transmission; two IP address management
<b>TCP/IP</b>	Tattile TCP/IP open protocol; two IP address management

### VIDEO STREAMING

<b>H.264/MPEG4</b>	Color video streaming H.264 or MPEG4
--------------------	--------------------------------------

### OPERATING MODE

<b>Free Run</b>	Continuous processing with automatic plate detection
-----------------	--

## TECHNICAL FEATURES

### SYSTEM

<b>ANPR Camera</b>	1920 x 1080 Monochrome CMOS sensor (cropped to 1280x1024 for the Short Range version)
<b>Context camera</b>	1920x1080 Color CMOS sensor (cropped to 1280x1024 for the Short Range version)
<b>Illuminator</b>	6 high power LEDs, InfraRed @ 850 nm (Short Range version) 10 high power LEDs, InfraRed @ 850 nm (Long Range version)
<b>Lenses</b>	F-Mount. Many focal length available.
<b>Operating System</b>	Linux
<b>Connectors</b>	Waterproof circular connector
<b>Network</b>	Fast Ethernet 10/100 and WiFi 802.11 b/g/n
<b>Storage</b>	Up to 16 GB

### ENVIRONMENT, SIZE, POWER

<b>Operating &amp; Storage Temperature</b>	From -30° to +55° C
<b>Operating &amp; Storage Humidity</b>	From 10% to 90% non condensing
<b>Dimensions</b>	178 x 141 x 76 mm (LxWxH)
<b>Weight</b>	1.5 kg
<b>Protection</b>	Waterproof IP66
<b>Power supply voltage</b>	12 Vdc
<b>Power consumption</b>	15 W